


## MINI CONTAORE

Typo: **CONTAHK30**

### Highlights

- Price competitive meter
- Excellent quality
- Long lifetime
- Different models for different markets
- All necessary approvals
- Your branding available





## MINI HOURCOUNT

Type: **CONTAHK30**

### Applications

- Gen-sets
- Compressors
- Pumps
- Medical equipment
- Control panels
- Air conditioning



Mechanical data	
Front dimension	36 x 24 mm (standard)
Display	DC: 5 integers, 2 decimals DC: 6 integers, 1 decimals without reset
Digit height	4 mm
Digit color	integer: white on black decimal: 50 Hz - red on black 60 Hz - white on black
Counting range	AC: 99999,99 h, DC: 99999,99
Reading accuracy	AC: 1/100 h (36 sec)
Weight	ca. 32 g
Housing color	standard black transparent on request
Bezels for 36x24 mm	48x24, 48x48, 54x29, 55x55, Ø 58, Ø 72, 72x72 mm
Mounting options	D - DIN housing E - 48x48 DIN case G - front 36x24 mm with retainer R - front 40,6x27,5 mm (1,60x1,08") with retainer S - 2-screw front 52x26mm (2,05x1,03")

Electrical data	
Operating voltage	24, 48, 60, 110, 120, 220, 230, 240, 400 VAC ± 10%, 50 or 60 Hz
	6-12, 12-36, 36-80, 110, 220 VDC ± 10%
Current consumption	AC: max. 8 mA DC: max. 9mA
Accuracy	AC: ± 0,02% DC: ± 0,002 %
Connection	flat pin 6,3x0,8 with screw flat pin 6,3x0,8

Ambient conditions	
Operating temperature	AC: -25°C .. +70°C DC: -10°C .. +55°C
	Storage temperature
Relative humidity	max. 80% at +25°C
Protection	IP40 front IP67 front (transparent housing) IP67 totally sealed housing IP00 terminals
Approvals	CE Mark UL E171200 RoHS compliant